

Store Inventory Report ending May- 2020 .

Name of the Division- Yamuna Colony Dehradun

Name of the SubDivision- 132 KV S/S Laltappar.

1	2	3	4	5	6	7	8	9	10
SN	Name of item /mate rail	Unit of measure ment(Nos /km/kg etc)	Quantity of materials Usabl	Rate	Amount	Dismantle	Incompleted	Damage	Obsolete
1	132 KV CB Closing coil(Spare)	Nos	3	3013	9039	-	-	-	-
2	132 KV CB Tripping coil(Spares)	Nos	3	3013	9039	-	-	-	-
3	132 KV CB Gas filling equipment(spares)	Nos	1	35550	35550	-	-	-	-
4	132 KV CB Gas Leakage detector(spares)	Nos	1	42117	42117	-	-	-	-
5	132 kv CB SF6 Gas cylinder 50 KG(spares)	Nos	1	162683	162683	-	-	-	-
6	132 Kv CB gas filling and Evacuation Equipment.	Nos	1	198835	198835	-	-	-	-
7	132 kv Isolator copper contact finger(spares)	Nos	1	21691	21691	-	-	-	-
8	132 KV Isolator rotary bearing(spares)	Nos	1	3615	3615	-	-	-	-
9	132 KV Isolator Terminal Pads (spares)	Nos	1	723	723	-	-	-	-
10	33 KV CB Closing coil(Spare)	Nos	6	1808	10848	-	-	-	-
11	33 KV CB Tripping coil(Spare)	Nos	6	1808	10848	-	-	-	-
12	33 kv Isolator copper contact finger(spares)	Nos	1	12051	12051	-	-	-	-
13	Set of Illumination lamp one set each type	Nos	1	10846	10846	-	-	-	-
14	Set of Control switch one set each type (total 4 nos are present)	Nos	1	14461	14461	-	-	-	-
15	Set of Aux. Relay one no each type(total 3 relay are present)	Nos	1	42177	42177	-	-	-	-
16	Set of Trip Relay one no each type(total 3 relay are present)	Nos	1	964068	964068	-	-	-	-
17	Trip coil supervision type TSR Aux. 110V , Dc model no-1N352-001-AS	Nos	1	4500	4500	-	-	-	-
18	Master trip relay model no- RK251206AN	Nos	1	664048	664048	-	-	-	-
19	Push button for resetting M.NO-IN3963001-AC	Nos	1	1250	1250	-	-	-	-
20	DC Supervision relay 110V DC ,MNO-INRK27019AN	Nos	1	6670	6670	-	-	-	-
21	DC Changeover relay110V DC INRK21105-2AN	Nos	1	8576	8576	-	-	-	-
22	DC fail acceptance relay 240V AC M.NO-INRK211052BS	Nos	1	14383	14383	-	-	-	-
23	AC Supervision Relay 240V AC M.NO-INRK211052BS	Nos	1	6798	6798	-	-	-	-
24	Transfrmer trouble relay 110V DC INRK271018AN	Nos	1	300000	300000	-	-	-	-
25	Amber colour LED indicating Lamp110V DC	Nos	1	1550	1550	-	-	-	-
26	White colour LED indicating Lamp110V DC	Nos	1	1550	1550	-	-	-	-
27	Break control switch T-N-C 25 amp	Nos	1	3615	3615	-	-	-	-
28	Isolator control switch 3 position 4 way 25 amp	Nos	1	4615	4615	-	-	-	-
29	Trip transfer switch 3 position 20 way 25 amp	Nos	1	2600	2600	-	-	-	-

30	Voltmeter selector switch 4 position 25 amp	Nos	1	3631	3631	-	-	-	-
31	Neutral bushing complete with gasket(spares)	Nos	2	64579	129158	-	-	-	-
32	36 KV bushing complete with(spares)	Nos	2	42890	85780	-	-	-	-
33	Set of Gasket for tank cover & fitting (spares)	Nos	2	12450	24900	-	-	-	-
34	Flow indicator	Nos	2	32900	65800	-	-	-	-
35	Contact thermometer of each type(spares)(total 4 are present)	Nos	2	4200	8400	-	-	-	-
36	Bochholz Relay each type (spares)	Nos	2	23500	47000	-	-	-	-
37	Oil level indicator of each type (150 mm dia 2 nos & 100 mm dia 2 nos) (spares)	Nos	2	45500	91000	-	-	-	-
38	Pressure releif device of each type(spares)	Nos	2	46281	92562	-	-	-	-
39	Bushing CTs of each type (spares) (total 4 in which 2 hv & 2 lv)	Nos	2	18500	37000	-	-	-	-
40	Transformer power oil	Ltrs	209	80	16720	-	-	-	-
41	Jack for jacking the transformer	Nos	8	1500	12000	-	-	-	-
42	Sling fitting device for transformer	Nos	2	2500	5000	-	-	-	-
43	Empty transformer oil drums	Nos	159	50	7950	-	-	-	-
44	Empty Acid cans	Nos	49	80	3920	-	-	-	-
45	11 KG empty SF6 Gas cylinder	Nos	5	4500	22500	-	-	-	-
46	PVC cable 2.5 sq mmx10 core	KM	0.148	215104	31835.39	-	-	-	-
47	PVC cable 2.5 sq mmx 6 core	KM	0.382	130508	49854.06	-	-	-	-
48	HF cable	KM	1.792	179455	321583.36	-	-	-	-
49	M.S Flat 50x 6 mm	MT	0.313	25000	7825.00	-	-	-	-
50	Earthing Material M.S round 36 mm dia	MT	0.091	19600	1783.6	-	-	-	-
51	Main and auxialry structure, Bolts & nuts(Lattice structure & Hardware)	MT	0.265	71099	18841.24	-	-	-	-
52	ACSR Zebra conductor	KM	0.165	231471.8	38192.85	-	-	-	-
53	ACSR Panther conductor	KM	1.06	100000	106000	-	-	-	-
54	AAC Tarantula conductor	KM	0.175	257000	44975	-	-	-	-
55	Suspension fitting for ACSR panther conductor	Nos	17	1808	30736	-	-	-	-
56	Disc Insulator	Nos	91	281	25571	-	-	-	-
57	Submersible Pumping set 7.5 Hp	Nos	1Set	35000	35000	-	-	-	-
58	Panel Board 7.5 Hp	Nos	1Set	8250	8250	-	-	-	-
59	Chain pulley block 02 m.t capacity	Nos	1Set	12200	12200	-	-	-	-
60	Wrench	Nos	1Set	1600	1600	-	-	-	-
61	Pipe clamp	Nos	1Set	400	400	-	-	-	-
62	Monoblock pump 5 Hp 3 phesh	Nos	1Set	27000	27000	-	-	-	-
63	Street light fitting suitable for 40 watt 4 feet long flouroscent day /light tube complete with all accessories along with L shape G.I pipe& clamps	Nos	1	1248	1248	-	-	-	-
64	10 mm2 , PVC insulated , 4core ,alluminium cable of good quality and reputed company	Mtr	50	111	5550	-	-	-	-
65	415 volt,50 hz,15 amp M.C.C.B of good quality and reputed company	Nos	1	2271	2271	-	-	-	-
66	Red,Yellow and Blue colour ,10 meter long copper testing lead having rolling drums.	Nos	3	559	1677	-	-	-	-

67	Street light fitting suitable for 85 watt worm white day /light lamp complete with all accessories along with L shape G.I pipe& clamps	Nos	1	4479	4479	-	-	-	-
68	250 volt, 50 Hz, electronic Ignitor	Nos	4	375.53	1502.12	-	-	-	-
69	415 volt, 6Amp, 50 Hz HRC Fuses	Nos	11	185.46	2040.06	-	-	-	-
70	132 KV Al made C.T clamp	Nos	4	1133.6	4534.4	-	-	-	-
71	132 KV Al made Isolator clamp	Nos	1	1133.6	1133.6	-	-	-	-
72	Heater Blower	Nos	1	5702	5702	-	-	-	-
73	Air Blower(Dust Cleaner), 230 volt,50 hz	Nos	1	5610	5610	-	-	-	-
74	2 * 3 feet size, 10 mm thick corksheat.	Nos	1	5709	5709	-	-	-	-
75	2 * 3 feet size, 8 mm thick corksheat.	Nos	1	5118	5118	-	-	-	-
76	33 kv Isolator clamp	Nos	5	1133.6	5668	-	-	-	-
77	33 kv CT clamp	Nos	5	1133.6	5668	-	-	-	-
78	132Kv, 1250 Amp Isolator copper contact male and female with arm complete set for P.R engineering works make isolators. As per sample.	Nos	3	24388.50	73165.5	-	-	-	-
79	33 Kv, 800 Amp isolator jaw and blade made of copper complete set for P.R engineering works make isolators. As per sample.	Nos	3	13385.00	40155	-	-	-	-
80	132 kv C.T clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	2	820.00	1640	-	-	-	-
81	132 kv C.V.T clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	3	820.00	2460	-	-	-	-
82	132 kv L.A clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	4	820.00	3280	-	-	-	-
83	132 kv C.B clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	4	820.00	3280	-	-	-	-
84	132 kv Transformer bushing clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	820.00	4920	-	-	-	-
85	132 kv Isolator clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	920.00	5520	-	-	-	-
86	132 kv Isolator clamps for zebra conductor made of aluminium alloy including all nut & bolt etc.	Nos	1	920.00	920	-	-	-	-
87	132 kv C.B clamps for zebra conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	920.00	5520	-	-	-	-
88	33 kv Transformer bushing clamps for tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	920.00	5520	-	-	-	-
89	33 kv C.T clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	920.00	5520	-	-	-	-
90	33 kv P.T clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	980.00	5880	-	-	-	-

91	33 kv Isolators clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	980.00	5880	-	-	-	-
92	33 kv C.B clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	980.00	5880	-	-	-	-
93	33 kv L.A clamps for Tarantula conductor made of aluminium alloy including all nut & bolt etc.	Nos	4	920.00	3680	-	-	-	-
94	33 kv C.T clamps for Panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	3	920.00	2760	-	-	-	-
95	33 kv Isolators clamps for Panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	5	920.00	4600	-	-	-	-
96	33 kv P.T clamps for panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	6	920.00	5520	-	-	-	-
97	33 kv C.B clamps for Panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	3	920.00	2760	-	-	-	-
98	33 kv L.A clamps for Panther conductor made of aluminium alloy including all nut & bolt etc.	Nos	4	920.00	3680	-	-	-	-
99	Run through clamps for 132 kv post insulators made of aluminium alloy including all nut & bolt.	Nos	1	920.00	920	-	-	-	-
100	Run through clamps for 33kv post insulators made of aluminium alloy including all nut & bolt.	Nos	1	920.00	920	-	-	-	-
101	HRC Fuses rating of 32 Amp, TIA type for 48 volt, 300 AH battery charger.	Nos	7	257.24	1800.68	-	-	-	-
102	250 volt, 50 Hz, electronic ignitor suitable for 250 watt HPSV Lamp	Nos	1	383.45	383.45	-	-	-	-
103	Old and used Transformer oil.	Ltrs	72	30	2160.00	-	-	-	-
104	Red colour, 230 Volt, 6 amp, spring return push-button switch.	Nos	5	405	2025.00	-	-	-	-
105	Green colour, 230 Volt, 6 amp, spring return push-button switch.	Nos	4	412	1648.00	-	-	-	-
106	Iron make danger plate having monogram of skull and bone on plate of size 215mm*300 mm having 02 no. 8-10 mm hole.	Nos	10	492	4920.00	-	-	-	-
107	3-way on-off 60 degree, 6 Amp, single pole selector switch of front side 5 c.m x 5 c.m.	Nos	11	330	3630.00	-	-	-	-
108	Double pole M.C.B of 240 volt, 50 Hz, 6 Amp.	Nos	3	1238	3714.00	-	-	-	-
109	Metal safety guard panel locks complete with lock, nut, washer.	Nos	4	328	1312.00	-	-	-	-
110	Fuse base with fuse holder suitable for HRC fuses of rating 20 Amp, 415 volt, 2.7 watt, single pole fot.	Nos	6	572.3	3433.80	-	-	-	-
111	Thermal over load relay of rated voltage 500 volt A.C, 50 Hz, over current range 0.9 Amp- 1.5 Amp.	Nos	1	2932.3	2932.30	-	-	-	-

(Signature)
(56)

112	3 phase digital Ampere-meter for measuring line current auxiliary voltage 110 volt D.C, CTR 800/1, accuracy class 0.5.	Nos	3	3835	11505.00	-	-	-	-
113	3- phase secure energy meters	Nos	6	5000	30000.00	-	-	-	-
114	Red color 220 volt A.C. Indicating lamp	Nos	3	300.9	902.70	-	-	-	-
115	Yellow color 220 volt A.C. Indicating lamp	Nos	4	285.56	1142.24	-	-	-	-
116	Blue color 220 volt A.C. Indicating lamp	Nos	4	286.74	1146.96	-	-	-	-
117	Green color 220 volt A.C. Indicating lamp	Nos	4	295	1180.00	-	-	-	-
118	Transparent clear plastic sheet, minimum thickness 2-3 mm.	Sq. feet	25	110.92	2773.00	-	-	-	-
119	Trip close with pistol grip handle 16Amp, 415Volt cam type spring return to neutral	Nos	3	1746.4	5239.20	-	-	-	-
120	Local Remote switch having specification 16Amp, 415V, Cam stayput type	Nos	3	1746.4	5239.20	-	-	-	-
121	Anti pumping relay 05Amp, 110V DC operated	Nos	1	885	885.00	-	-	-	-
122	Auxiliary contacts Normally Open contact 08 nos. and auxiliary contact Normally close contact 08 nos.	Nos	1	9322	9322.00	-	-	-	-
123	Double pole M.C.B 240V DC, Breaking capacity 10KA, Rating Amp- 32Amp DC	Nos	2	1711	3422.00	-	-	-	-
124	Double pole M.C.B 240V DC, Breaking capacity 10KA, Rating Amp- 16Amp DC	Nos	3	1298	3894.00	-	-	-	-
125	Double pole M.C.B 240V DC, Breaking capacity 10KA, Rating Amp- 06Amp DC	Nos	20	1805.4	36108.00	-	-	-	-
126	Double pole M.C.B 240V AC, 50Hz, Breaking capacity 10KA, Rating Amp- 32Amp AC	Nos	2	1180	2360.00	-	-	-	-
127	Double pole M.C.B 240V AC, 50Hz, Breaking capacity 10KA, Rating Amp- 16Amp AC	Nos	4	1298	5192.00	-	-	-	-
128	Double pole M.C.B 240V AC, 50Hz, Breaking capacity 10KA, Rating Amp- 06Amp AC	Nos	16	1793.6	28697.60	-	-	-	-
129	Aluminium Alloy Mechanical Bolt less C- Wedge Connector suitable for ACSR Zebra to Zebra Conductor containing one 'C' Body, one wedge with oxide inhibitor as per IS 5561 : 1970	Nos	3	3687.5	11062.50	-	-	-	-
130	Aluminium Alloy Mechanical Bolt less C- Wedge Connector suitable for ACSR Zebra to Panther Conductor containing one 'C' Body, one wedge with oxide inhibitor as per IS 5561 : 1970	Nos	6	3687.5	22125.00	-	-	-	-
131	Aluminium Alloy Mechanical Bolt less C- Wedge Connector suitable for ACSR Panther to Panther Conductor containing one 'C' Body, one wedge with oxide inhibitor as per IS 5561 : 1970	nos	7	3587.2	25110.40	-	-	-	-
132	Aluminium Alloy Mechanical Bolt less C- Wedge Connector suitable for ACSR Tarantula to Tarantula Conductor containing one 'C' Body, one wedge with oxide inhibitor as per IS 5561 : 1970	nos	5	3929.4	19647.00	-	-	-	-
133	Aluminium Alloy Mechanical Bolt less C- Wedge Connector suitable for ACSR Tarantula to Panther Conductor containing one 'C' Body, one wedge with oxide inhibitor as per IS 5561 : 1970	nos	7	3941.2	27588.40	-	-	-	-


[Handwritten signature]
[Handwritten initials]

134	Blue color 220 volt A.C. Indicating lamp.	nos	4	356.4	1425.60	-	-	-	-	-
135	White color 220 volt A.C. Indicating lamp.	nos	4	371.7	1486.80	-	-	-	-	-
136	Panther to Panther conductor P.G. clamp with all nut and bolt.	nos	6	961.7	5770.20	-	-	-	-	-
137	HRC fuses rating of 2 Amp, 415 volt A.C rated short circuit capacity 80 KA.	nos	22	108.6	2389.20	-	-	-	-	-
138	HRC fuses rating of 4 Amp, 415 volt A.C rated short circuit capacity 80 KA.	nos	21	120.4	2528.40	-	-	-	-	-
139	25 mm x 80 mm (WxH) size wiring cable duct.	mtr	8	531	4248.00	-	-	-	-	-
140	Best quality door limit switch with push rod of 1 NO+1 NC, 10 Amp, 500 Volt.	Nos	7	580.56	4063.92	-	-	-	-	-
141	1 NC, 3 phase power contactor having specification of Ith= 26 Amp., Iec= 25 Amp.	Nos	4	1451.4	5805.60	-	-	-	-	-
142	Panel mounting type electronic hooter of size 96 mm x 96 mm x 60 mm, I/P Volt.- 80-140 volt AC/DC or 280 Volt AC/DC.	Nos	1	2802.5	2802.50	-	-	-	-	-
143	25-75 degree temperature control thermostate suitable for 80 watt, 250 volt rating space heater.	Nos	5	584.1	2920.50	-	-	-	-	-
144	Power contactor 440 volt, 3 phase main pole and 1 inbuilt auxiliary contact with front side add-on facility rating of contactor.	Nos	3	1932.8	5798.40	-	-	-	-	-
145	Power contactor of 220 volt, I= 6amp., DC coil voltage= 110 Volt d.c.	Nos	1	2920.5	2920.50	-	-	-	-	-
146	voltage monitoring relay/ Phase failure relay having the under voltage and over voltage setting.	Nos	1	3540	3540.00	-	-	-	-	-
147	Contactor Add On Block (Additional instantaneous auxiliary contact blocks) having front mounted of 2 NO+ 2NC.	Nos	6	955.8	5734.80	-	-	-	-	-
148	Moving coil D.C. analog voltmeter of size 9.3*9.3 c.m suitable for measuring of D.C. volt. Range 0-200 volt.	Nos	1	2891	2891.00	-	-	-	-	-
149	Moving Iron A.C. analog Ampere meter C.T. ratio 30/5 amp. Of size 9.3* 9.3 c.m.	Nos	1	2891	2891.00	-	-	-	-	-
150	32 Amp. , 500 volt fuse fitting (Base and carrier.	Nos	8	725.7	5805.60	-	-	-	-	-
151	Red color 2 inch * 2 feet size high intensity reflective tape.	Nos	4	519.2	2076.80	-	-	-	-	-
152	Yellow color 2 inch * 2 feet size high intensity reflective tape.	Nos	3	519.2	1557.60	-	-	-	-	-
153	Blue color 2 inch * 2 feet size high intensity reflective tape.	Nos	3	519.2	1557.60	-	-	-	-	-
154	Aluminium scrap.	kg	-	12	96.00	-	-	-	-	-
155	132 KV Transformer bushing complete.	Nos	2	75493	150986.00	-	-	-	-	-
156	250 volt, 50 Hz, 33 MFD condensers suitable for 250 watt HPSV Lamp light.	Nos	6	418.9	2513.40	-	-	-	-	-
157	overload relay of range 0.4 – 0.63 Amp., auxiliary contact 1NO+1NC, single phase protection, Ambient temperature compensated, test button for checking tripping mechanism, contactor mounted.	Nos	2	2889.2	5778.40	-	-	-	-	-
158	415 volt, 63 Amp. rewire-able (porcelain fuse carrier & base) kit- kat fuse	Nos	8	585.28	4682.24	-	-	-	-	-

[Handwritten signature]

159	415 volt, 3phase D.O.L (Direct on line) starter of 5 HP mono-block pump	Nos	1	5888.2	5888.2	-	-	-	-
160	Galvanized steel earth wire tension clamp for 7/10 SWG Earth wire.	Nos	5	1170.56	5852.8	-	-	-	-
161	Galvanized steel earth wire Suspension clamp for 7/10 SWG Earth wire.	Nos	5	1170.56	5852.8	-	-	-	-
162	Galvanized Steel Mid span compression joint for Earth wire of 7/10 SWG Earth wire.	Nos	8	731.6	5852.8	-	-	-	-
163	Mid span compression joint for ACSR Panther conductor with steel and Aluminium portion.	Nos	4	1469.1	5876.4	-	-	-	-
164	3- Phase Digital voltmeter measuring of 33 KV, PTR 33KV/110 V, Auxiliary voltage 110 Volt.	Nos	4	2465	9860	-	-	-	-
165	110 volt, 500 AH Statcon make Battery Charger.	Nos	1	71400	71400	-	-	-	-
166	EHV Grade Transformer oil.	Nos	5	15357.1	76785.55	-	-	-	-
167	Metal cutter machine, Input 220-230 Volt, 670 watt.	Nos	1	5805.6	5805.6	-	-	-	-
168	Stud type terminal, suitable for 10 mm ² cable, 1000 v., 67 Amp.	Nos	11	151.04	1661.44	-	-	-	-
169	Stud type terminal, suitable for 16 mm ² cable, 1000 volt, 76 Amp.	Nos	9	167.56	1508.04	-	-	-	-
170	Stud type terminal, suitable for 25 mm ² cable, 1000 volt, 100 Amp.	Nos	10	230.1	2301	-	-	-	-
171	Red Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 64 Amp, Ig=32 Amp, wire size Incoming= 25 mm ² , Outgoing= 4 mm ² .	Nos	5	387.04	1935.2	-	-	-	-
172	Yellow Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 64 Amp, Ig=32 Amp, wire size Incoming= 25 mm ² , Outgoing= 4 mm ² .	Nos	5	387.04	1935.2	-	-	-	-
173	Blue Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 64 Amp, Ig=32 Amp, wire size Incoming= 25 mm ² , Outgoing= 4 mm ² .	Nos	5	387.04	1935.2	-	-	-	-
174	Red Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 300 Amp, log=100 Amp, wire size Ic= 150 mm ² , log= 25 mm ² .	Nos	2	967.6	1935.2	-	-	-	-
175	Yellow Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 300 Amp, log=100 Amp, wire size Ic= 150 mm ² , log= 25 mm ² .	Nos	2	967.6	1935.2	-	-	-	-
176	Blue Color, Distribution block of 1*4 typesuitable for 800 volt, Ic= 300 Amp, log=100 Amp, wire size Ic= 150 mm ² , log= 25 mm ² .	Nos	2	967.6	1935.2	-	-	-	-
177	Moving Iron A.C. Analog Voltmeter of size 9.3 c.m* 9.3 c.m	Nos	1	2891	2891	-	-	-	-
178	Silica gel of size 20-25 mm Blue crystal.	kg	30	389.4	11682	-	-	-	-
179	A- Grade Petroleum Jelly.	kg	12	450.76	5409.12	-	-	-	-
180	Din Rail mounted Power terminals of rating volt.- 1000 Volt, rating current Ic- 125 Amp.	Nos	5	578.2	2891	-	-	-	-

181	Din Rail mounted Power terminals of rating volt.- 1000 Volt, rating current Ic- 150 Amp.	Nos	5	578.2	2891	-	-	-	-
182	3 phase 3 way connector made of poly carbonate, rating 440 volt A.C.	Nos	12	241.3	2895.6	-	-	-	-
183	3 phase 4 way connector made of poly carbonate, rating 440 volt A.C.	Nos	12	241.3	2895.6	-	-	-	-
184	Din Rail mounted Plug &Socket terminal of min. 2 way of rating Volt- 800 V A.C, Rating Ic= 32 Amp	Nos	8	243.08	1944.64	-	-	-	-
185	Din Rail mounted Plug &Socket terminal of min. 4 way of rating Volt- 800 V A.C, Rating Ic= 32 Amp	Nos	8	243.08	1944.64	-	-	-	-
186	Din Rail mounted Plug &Socket terminal of min. 8 way of rating Volt- 800 V A.C, Rating Ic= 32 Amp	Nos	8	243.08	1944.64	-	-	-	-
187	3-Phase Digital MVAR meter of CTR 400/1, PTR 33KV/110 V Aux. Volt- 110 V DC.	Nos	2	5876.4	11752.8	-	-	-	-
188	Sliding link Type Disconnecting Terminal, Rated Volt- 800 V, Rated Current- 41 Amp, wire size- 6 mm ² .	Nos	12	236	2832	-	-	-	-
189	Neutral Link mounted with insulating Pad.	Nos	10	300.9	3009	-	-	-	-
190	220 Volt, 36 watt electronic ballast for TL-D Lamp.	Nos	2	1162.3	2324.6	-	-	-	-
191	Side mounting ADD- ON Aux. contactor block of 1NO+1NC.	Nos	8	728.06	5824.48	-	-	-	-
192	3-Phase Ammeter selector switch of rating 6 Amp, having 4 position, OFF-R-Y-B, deach position 90 degree.	Nos	4	702.1	2808.4	-	-	-	-
193	3-Phase Ammeter selector switch of rating 10 Amp, having 4 position, OFF-R-Y-B, deach position 90 degree.	Nos	3	991.2	2973.6	-	-	-	-
194	Exhaust type cooling fans with technical specification as- Voltage- 415 volt, Impeller Dia- 600 mm, 3 phase, 6 pole, I/P Power -550 watt, speed 950 r.p.m.	Nos	3	18868	56604	-	-	-	-
195	O.T.I meter of temperature range 0-150 Degree celcius, accuracy class +/-1 1%FSD, Dia size 150mm, Dial angular sweep- 270 degree.	Nos	1	29500	29500	-	-	-	-
196	W.T.I meter of temperature range 0-150 Degree celcius, accuracy class +/-1 1%FSD, Dia size 150mm, Dial angular sweep- 270 degree.	Nos	1	30680	30680	-	-	-	-
197	HPSV lamps of lamp wattage- 250 watt, Rated voltage- 240 volt.	Nos	6	973.5	5841	-	-	-	-
198	Aluminium scrap.	kg	0.4	12	4.8	-	-	-	-
199	Slotted type DIN RAIL of dimension 35*15*1.5 mm (width*height*thickness).	Nos	10	351.64	3516.4	-	-	-	-
200	slotted type DIN RAIL of dimension 35*7.5*1.5 mm (width*height*thickness).	Nos	10	233.64	2336.4	-	-	-	-
201	250 watt, 220 volt, 50 Hz electronic chock.	Nos	3	1956.44	5869.32	-	-	-	-


 Junior Engineer
 132 KV S/S Lal Tappar