



सिलवासा नगर पालिका
SILVASSA MUNICIPAL COUNCIL
संघशासित प्रदेश दादरा एवं नगर हवेली एवं दमन एवं दीव
U.T. of DADRA & NAGAR HAVELI AND DAMAN & DIU
सिलवासा ३९६ २३० / SILVASSA – 396 230



ई-मेल/E-mail: silvassamunicipalcouncil@gmail.com
Phone No.: 0260-2633193, Mobile No.: +91 8347472611
Website: smcdnh.in

No. SMC/CO/Civil/Repair/2025/64/6003

Date:- 03/10/2025

Subject: - “Restoration of damaged false-ceiling at Silvassa Municipal Council Bhavan, Silvassa”.

:- LIMITED TENDER NOTICE NO. 08 OF 2025-26 :-

On behalf of the President of India, the Chief Officer, Silvassa Municipal Council, Dadra & Nagar Haveli, Silvassa has invites sealed limited tender/bid from interested Agencies/Contractors/firms for the work of “Restoration of damaged false-ceiling at Silvassa Municipal Council Bhavan, Silvassa” so as to reach to undersigned on or before 07/10/2025 up to 13.00 hours by post/courier or by hand delivery.

Sr. No.	Description of item	Qty.	Unit	Rate (in Rs.)	Amount (Including GST)
1.	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge	37.00	Sqm.		
2.	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm	16.00	Sqm.		

	centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) :2011 (Board with BIS certification marks)				
3.	Providing and Fixing 15 mm thick densified tegular edged eco friendly light weight calcium silicate false ceiling tiles of approved texture of size 595 x 595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross "T" of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to form grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size(24x24X3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450 mm centre to centre with 25 mm long dry wall screws @ 230 mm interval and laying 15 mm thick densified edges calicum silicate ceiling tiles of approved texture in the grid, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc., wherever required. Main 'T' runners to be suspended from ceiling using	39.00	Sqm.		

	G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24 mm of all Tsections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawings and as directed by Engineer-in-Charge.				
4.	Providing and fixing Gypsum Tiles Fully Perforated Square edge of Size 595x595 mm and 12.5 mm thick.	5.00	Sqm.		
5.	Applying two coats of putty & two coats of primer of approved brand and manufacture on new wall surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.	18.00	Sqm.		
6.	Wall painting (two coats) with plastic emulsion paint of approved brand and manufacture on undecorated wall surface to give an even shade including throughly brushing the surface free from mortar droppings and other foreign matter and sand papered smooth.	18.00	Sqm.		
Total (Rs.)					

Terms & conditions are as under:-

- The rates quoted by the contractor/agency shall include all taxes including GST and nothing extra shall be payable on account of taxes for the work executed.**
- Sealed envelope should be superscribed word **“Restoration of damaged false-ceiling at Silvassa Municipal Council Bhavan, Silvassa”**.
- The work should be completed within the prescribed time limit given by this Department.
- The payment will be after full satisfaction of the representative of the Department.
- The Agencies/Contractors should quote their rates in their own letter pad OR on plain paper with their rubber stamp.
- The rates should be valid up to 31/12/2025.
- Tender Fees of Rs.500/- should be submitted in favour of the undersigned (Chief Officer, Silvassa Municipal Council) in the form of a Demand Draft.
- EMD for an amount of Rs. 2280/- (Rupees Two Thousand Two Hundred Eighty Only) should be submitted in favour of the undersigned (Chief Officer, Silvassa Municipal Council) in the form of Demand Draft/Fixed Deposit Receipt.

9. The Tenders shall be considered invalid and non-responsive for non-submission of any document stipulated herein. (Tender Fees, EMD)
10. The tender form is also available on website address <https://dnh.gov.in/#Tenders> and <https://ddd.gov.in/#Tenders> which can be downloaded and used for submitting the tender in the manner prescribed above along with the cost of the tender document and EMD.
11. The intending Contractors/ bidders should submit their documents by RPAD/Speed post or by hand to the Silvassa Municipal Council, Silvassa office. However, the tender inviting authority shall not be responsible for any postal delay/lost of documents demanded. The said documents can also be deposited in the Tender Box kept at the office of the undersigned on or before 07/10/2025 up to 01.00 hrs.
12. The tenders shall be opened on /10/2025 at 02:00 Hrs. in the presence of the bidders if any.
13. The Department of Silvassa Municipal Council reserves their right to accept or reject any or all bids without giving any reason thereof is reserved by the undersigned.

Sd/-
Chief Officer
Silvassa Municipal Council
Silvassa

Copy to:-

1. The President, Silvassa Municipal Council, Silvassa, for kind information, please.
2. All Head of Office, D&NH, Silvassa, for kind information and vide publicity.
3. The Assistant Director (IT), DNH, Silvassa with request to uploading in DNH Administration Website and Silvassa Municipal Council official website (www.smcdnh.nic.in).
4. Notice Board.