



जिल्हा परिषद धाराशिव, बांधकाम विभाग

पहिला मजला, जिल्हा परिषद प्रशासकीय इमारत, धाराशिव - 413503

दूरध्वनी क्र - 02472-22059 Email ID : exeenggworksddharashiv@gmail.com



स्वातंत्र्याचा अमृत महोत्सव

क्रमांक: जिपधा / बांवि / विद्युत / कावि / 38 / 2025

दिनांक :- 16/07/2025

दरपत्रक सूचना

(दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी सीलबंद दर पत्रक मागविणे बाबत)

कार्यकारी अभियंता, बांधकाम विभाग, जिल्हा परिषद, धाराशिव यांच्या कार्यालयामार्फत 'कै. यशवंतराव चव्हाण सभागृह येथे ध्वनीक्षेपक यंत्रणा बसविणे' या कामासाठी तयार करण्यात आलेल्या अंदाजपत्रकातील Non-CSR (Non-Schedule Rate) बाबींचे दर अंतिम करण्यासाठी पात्र व अनुभवी ठेकेदार, पुरवठादार व उत्पादकांकडून खाली नमूद केलेल्या उपकरणे व साहित्य यांची सीलबंद दरपत्रके मागविण्यात येत आहेत.

1. दरसूची बाह्य बाबींचा तपशील:

Sr. No	Details of Item (Non – CSR)	Unit	Estimated Rate Rs
1.	Supply, installation, & testing of Delegate Unit Microphone with flexible stem of Min. 488 mm in length and Bulit in loudspeaker Two, Headphone sockets Compact, attractive design Interconnections : 1 x 2.7 m (106.3 in) cable terminated with a 8-pin male connector for loop-through connection to other, 1 x 8-pin circular female connector for loop-through connection to other delegate or chairman units, 2 x 3.5 mm (0.14 in) stereo headphone sockets. Nominal Acoustic: Input at the microphone :85dB SPL Frequency Response : 400Hz to 10Khz Operating temperature : -5 °C to +45 °C Mounting: Tabletop. Make : Bosch (Model - CCSE-CML) or Similar	No's	
2.	Supply, installation, & testing of Chairman Unit ,Priority button for chairman microphone, Microphone with flexible stem of min 488 mm in length , Microphone with flexible stem and light ring Bulit in loudspeaker Two Headphone sockets compact, attractive design Controls and Indicators: Microphone on/off button ,Chairman priority button, Rotary volume control for adjusting headphone volume, Loudspeaker, automatically muted when microphone is on , Microphone 'on' indicator (red LED).Light ring indicator on microphone stem, lights up red when microphone is on. Nominal Acoustic: Input at the microphone :85dB SPL Frequency Response : 400Hz to 10Khz Operating temperature : -5 °C to +45 °C Mounting: Tabletop Make : Bosch (Model -CCSE-CML) or Similar	No's	

3.	Supply, installation, & testing of Control and Power supply Unit Supplies power to all contribution units. Two to Six Microphones can be active simultaneously. Controls upto 50 discussion units Interface system with external equipment like amplifier, mic etc. Built in 3 Band Equalizer for better sound Controls and Indicators :Equaliser comprising of knobs at 250Hz, 2kHz and 8kHz, Volume control for Mic 1 input, Volume control for Mic 2 / Aux input ,Headphone input and volume control, Master volume control, Sliding switch for Equaliser On/Off, Sliding switch to enable or disable the priority tone for chairman units, Number of Active microphone control knob Interconnections: Trunk input and output 8-pin DIN connectors for loop through connection, Microphone input with XLR connector, Configurable Mic or Aux input with 6.5mm phono jack, Cinch connectors for connecting to external PA system and recorder, Earth connection screw, Mains socket Mains voltage : 230VAC,50 Hz ($\pm 10\%$) , DC voltage supply to contribution units : 24V $\pm$ 1V DC , THD at rated output : <1% SNR : >-50dB at rated output (unweighted filter) Inputs : Mic input sensitivity - 1 mV (+1/-3dB) , Frequency response :200 Hz to 12 kHz , Input Impedance : 4.7 kohm , Center frequencies of filters : 250Hz,2kHz and 8kHz , PA Rated output Impedance :100 ohm , SNR : >-50dB at rated output (unweighted filter) REC Rated output Impedance : 1 kohm Operating temperature : -5°C to 45°C Make: Bosch (Model CSSE-CU) or Similar	No's	
4.	Supplying & erecting of Wireless and Microphones Professional Narrowband Quad-Channel, Antenna UHF Wireless Handheld Cardioid Microphone system with freq bandwidth: 480-934 MHz , diversity metallic receiver; battery status LCD in Tx and Rx; Synthesized PLL ,THD <0.8%; cardioid polar pattern; 32 selectable freq/band; S/N 100dBA . 14 Hours Battery Life. Make :- Mipro (Model : ACT-343) or Similar	No's	
5.	Supplying, Erecting, Testing and Commissioning of DCN Multi core Conference Cable 100 mtrs in Length. Technical specifications Mechanical Dimensions (dia.) 6 mm (0.24 in) Material PVC Colo Grey: Make :-Bosch (LBB 41161) / Mipro / Electro Voice or Similar	Mtr	
6.	Supplying & Erecting of Connector For Conference System Units For Loop Through. Make :- Bosch/Mipro/EV or Similar	No's	
7.	Supplying & Erecting of XLR M/F,Jack,RAC Connectors Make-Neutrik, MX or Similar make	No's	

8.	Supply, Installation, testing and commissioning of 8" Wall Mount Two Way Speaker: The wall mount speaker shall have: 8" or better woofer and 1" Tweeter or more, Should have multiple transformer Tapping option from of 60 watts down to 7.5watts or better. Should have 70watts RMS output power on low impedance, Impedance: 8 or 16 Ohms, The speaker shall have a Frequency Response ranging from 50Hz to 20kHz for better sound reproductivity, Max SPL: 105dB or more Should have metal grill made of steel or better, Horizontal and vertical dispersion angle: 105x105 degree or more etc complete required as per specifications etc. complete as required. Make:- AUDAC (Model:- WX802) or Similar	No's	
9.	Supply, installation, & testing of Dual Channel 2x1050W Power Amplifier High power and efficient design: 1050W (Stereo, into 4Ω) Driven by a newly developed Class-D amplifier engine. Stable 2-ohm drive capability. Supremely efficient amplifiers with low noise, reliable protection features. Amp Mode allows the user to configure the system without difficulty by selecting the input routing and output routing. Sophisticated signal processing allowing users to achieve consistent clarity and high-quality sound for either front-of-house or monitor configurations. Eight programmable presets for instant recall and reduced setup time that can be saved to a USB thumb drive and shared with other amplifiers. Preset specifically tuned for each model in Yamaha's extensive lineup of passive speakers. A variety of input and output terminals. Panel locking function to keep your settings safe. Make : Yamaha (Model : PX8) or Similar	No's	
10.	Supply, installation, & testing of 16 Channel Audio Mixer Input channels: 16 Line Inputs (8 mono, 2 stereo), 16 Mic Inputs with 48V phantom power and HPH per channel. Output channels: 1 ST out, 1 Mono out, 1 Monitor out, 2 AUX sends, 4 Group out, 1 Phones out, 2 Matrix out, 1 Stereo CH insert out, 16 Mono CH insert out. Buses: 1 Stereo bus, 4 Group buses, 4 AUX Sends Robust, impact-resistant, powder-coated metal chassis. Internal universal power supply for worry-free operation around the globe, even in unsteady voltage environment. Make : Yamaha (Model MG16 XU) or Similar	No's	

2. दर पत्रक सादर करण्याची दिनांक वेळ व पत्ता:

- सीलबंद लिफाफ्यामध्ये दरपत्रके सादर करण्याची दिनांक व वेळ :- दिनांक . 28/07/ 2025 वेळ सकाळी 10.00 ते दिनांक 29/07/ 2025 सायंकाळी वेळ 5.00 वाजेपर्यंत.
- दरपत्रके सादर करणे करिता पत्ता : कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव.
- दरपत्रके उघडण्याची वेळ : 29/07/ 2025 सकाळी वेळ 11:00 वाजता.

3. अटी व शर्ती:

1. दरपत्राकतील दर फक्त अंदाजपत्रक तयार करण्यासाठी वापरण्यात येतील.
2. कामाची सविस्तर माहिती व तांत्रिक तपशील कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव या कार्यालयाकडून प्राप्त करून घेण्यात यावी.
3. निविदादारांनी कामाची जागा, वाहतूक, मजुरी खर्च व साहित्य उपलब्धतेचा स्वतः अभ्यास करावा.
4. सर्व उपकरणे व काम BIS / IEC व तसेच इतर लागू असलेल्या मानकांनुसार असणे आवश्यक आहे.
5. दरामध्ये सामग्रीचा पुरवठा, स्थापनेपासून ते चाचणी पर्यंतचे सर्व काम, वाहतूक, विमा, वॉरंटी / गॅरंटी ई. समाविष्ट असावा.
6. सर्व दर G.S.T. वगळून देण्यात यावे.
7. पुरवठाधारक/ निविदाधारक हा Manufacturer / Integrator / Supplier / Developer आहे याची खात्री करणे करिता विभागाच्या मागणीनुसार आवश्यक दस्तऐवज सादर करणाऱ्यात यावे.
8. जिल्हा परिषद, धाराशिव दिलेल्या वस्तूंचे दर, गुणवत्तेची व तांत्रिक मानकांची पूर्तता तपासण्याचा अधिकार राखून ठेवला आहे.
9. खोटी अथवा दिशाभूल करणारी माहिती सादर केल्यास दरपत्रक फेटाळले जाईल व आवश्यक कार्यवाही करण्यात येईल याची नोंद घेण्यात यावी.
10. सदर बाबत कोणताही तंट्या अगर वाद निर्माण झाल्यास त्याबाबत कोणत्याही न्यायालयात दावा दाखल करता येणार नाही. याबाबत कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव किंवा जिल्हा परिषद धाराशिव मधील सक्षम प्राधिकारी यांचा निर्णय अंतिम राहील.
11. दरपत्रक दिलेल्या विहित नमुन्यातच आणि पाकिटावर विषय नमूद करून सादर करणे आवश्यक आहे.
12. मुदत संपल्यानंतर प्राप्त होणाऱ्या कोटेशनचा विचार केला जाणार नाही.
13. कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव किंवा जिल्हा परिषदेतील सक्षम प्राधिकारी यांनी कोणतीही कोटेशन नाकारण्याचा/स्वीकारण्याचा अधिकार राखून ठेवला आहे.


कार्यकारी अभियंता (बां)
बांधकाम विभाग, जिल्हा परिषद,
धाराशिव

- दरपत्रक सादर करावयाचा नमुना :

(ठेकेदार/ पुरवठादार लेटर हेड)

Date : / / 2025

दरपत्रक

प्रती,

मा. कार्यकारी अभियंता (बां)
बांधकाम विभाग,
जिल्हा परिषद , धाराशिव

विषय : दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी सीलबंद दरपत्रक मागविणे बाबत.

संदर्भ : आपले दरपत्रक मागणी पत्र

महोदय,

उपरोक्त विषयास अनुसरून सादर कि, संदर्भित पत्रान्वये 'कै. यशवंतराव चव्हाण सभागृह येथे ध्वनीक्षेपक यंत्रणा बसविणे' या कामातील दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी सीलबंद दरपत्रके मागविण्यात आले आहेत. त्यानुसार खलील प्रमाणे दरसूची बाह्य बाबींचे दर सादर करीत आहोत. सदर दर हे सामग्रीचा पुरवठा, स्थापनेपासून ते चाचणी पर्यंतचे सर्व काम, वाहतूक, विमा, वॉरंटी / गॅरंटी व संपूर्ण देखभाल करार (CMC) यांचा विचार करून निश्चित केलेले आहेत.

1. दरसूची बाह्य बाबींचा तपशील:

Sr. No	Details of Item (Non – CSR)	Unit	Estimated Rate Rs
1			
2			
3			

दर पत्रकासह सादर करण्यात येत असलेल्या बाबींचा तपशील.

1. पॅन आणि जीएसटीचा तपशील.
2. आयटी रिटर्नची प्रत.
3. कामाचा अनुभव प्रमाणपत्र.

आपला विश्वासू,

(सही व शिक्का)

(ठेकेदार/ पुरवठादार यांचे नाव व पत्ता)