



जिल्हा परिषद धाराशिव, बांधकाम विभाग

पहिला मजला, जिल्हा परिषद प्रशासकीय इमारत, धाराशिव - 413503

दूरध्वनी क्र - 02472-22059 Email ID : exeenggworksddharashiv@gmail.com



स्वातंत्र्याचा अमृत महोत्सव

क्रमांक: जिपधा / बांवि / विद्युत / कावि / 234 / 2026

दिनांक :- 02/04/2026

दरपत्रक सूचना

(दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी दुबार सीलबंद दर पत्रक मागविणे बाबत)

कार्यकारी अभियंता (बां) , बांधकाम विभाग, जिल्हा परिषद धाराशिव यांच्यामार्फत पात्र आणि अनुभवी ठेकेदार/ पुरवठादार दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी खालीलप्रमाणे सीलबंद दरपत्रक दि. 16.03.2026 ते दि. 23.03.2026 या कलावधी मध्ये मागविण्यात आले होते. तथापि सदर कलावधी मध्ये दरपत्रके प्राप्त न झाल्याने सदर कामाचे दरपत्रक दुबार (2'nd Call) मागविण्यात येत आहेत. जिल्हा परिषद धाराशिव आरोग्य विभाग अंतर्गत 45 प्राथमिक आरोग्य केंद्राच्या ठिकाणी सिसिटीव्ही कॅमेरा बसविणे या कामासाठी प्रस्तावित वस्तूंच्या दरांचे अंदाजपत्रक तयार करण्यासाठी हे दर वापरण्यात येतील.

1. दरसूची बाह्य बाबींचा तपशील:

Sr. No	Details of Item (Non – CSR)	Unit
1.	Supplying, installing, testing & commissioning of 16/20 Ch. Network Video Recorder (NVR), suitable for 2 MP cameras only with HDMI/VGA outputs provided HDMI output of 4K resolution or VGA output with output up to 1920 × 1080. Support H.265 or higher, H.264, MJPEG, Incoming Bandwidth 160Mbps with minimum 2 SATA Hard Disks, ANR Technology, 2 SATA interfaces for 2 HDDs and capacity of each HDD up to 8TB, minimum 02 USB port, Alarm I/O 4/1, RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface, support multi brand network Cameras, ONVIF conformance, Multiple network monitoring: Web viewer. support protocol TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS. RoHS, UL, CE, FCC certified. duly erected in provided U Rack with wiring connections, tagging and programming etc. complete as per specifications no. CCTV-NVR	Each
2.	Supplying & erecting 43" professional LED display with 1920*1080 (Full HD) Display, suitable for 16/32 channel NVR and following features Brightness: minimum 500 Cd/m2 Contrast Ratio: minimum 1000:1 Viewing angle: 178/178 deg. Response time: maximum 8 ms Inputs: HDMI, VGA, BNC,USB, Audio In, Built-in speakers maximum 10 W, Suitable to operate on 100-240 V 50 Hz AC supply and 24/7 Duty Cycle duly erected on wall or table top with standard accessories like wall mount stand and wiring connections etc. complete as per specifications no. CCTV-MON	Each

3.	<p>Supplying & erecting 4 TB internal Surveillance HDD suitable for SATA Port of NVR, interface transfer rate 6 GB/S, Maximum sustained transfer rate 150MB/Sec to 180MB/S. Drive bay supported 08+, Cameras supported up to 64, Cache (MB) 64, Load/Unload Cycle -3000000, Work Load Rating per Year 180TB, MTBF 1000000 Hrs. HTTPS. RoHS, UL, CE certified, duly erected in position in provided NVR as per specification no. CCTV-HDD</p>	Each
4.	<p>Supplying & erecting of High definition 4/5 Megapixel IP IR Bullet Camera with following features Image Sensor : minimum 1/2.8" Progressive Scan CMOS, Video Resolution : minimum 2592 x 1520 Video Compression : H.264, H.265 or higher, at least Three individually configurable stream, Frame rate : minimum 25 fps at all resolutions, WDR : minimum 120 dB Wide Dynamic Range, ONVIF profile conformant, minimum IR distance : 50m, Lens Type : 2.8/4/6 mm Lens, fixed focal, Field of View : 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 129° 4 mm, horizontal FOV 86°, vertical FOV 47°, diagonal FOV 102° 6 mm, horizontal FOV 55°, vertical FOV 29°, diagonal FOV 65° Lux sensitivity - minimum 0.2 Lux at color, minimum 0.05 Lux at Black & White, 0.0 Lux (IR) Night Vision Distance minimum IR - 50m. Camera minimum Adjustment Angles - Pan : 350°, Tilt : 72°, Rotate : 350°. Power Supply : Support 12VDC & PoE, IP67, IK10 - Vandal Resistant. Built in micro SD/SDHC/SDXC card slot of minimum 128 GB, Built in microphone. minimum Input/Output - Audio in × 1, Audio Out × 1, Alarm in × 1, Alarm Out × 1. Image Settings : Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance. Image Enhancements : Day/Night-Auto (ICR)/Color/Black & White, 3D Digital Noise Reduction, Automatic White Balance, Automatic Gain Control, Backlight Compensation, Highlight Compensation. Events : Privacy Masking, Motion detection, Scene change detection, Face capture, Video tampering, audio exception detection, Region entrance detection, Region exiting detection. Operating temperature (-30 to 60° C). Security - User account and password protection, HTTPS, IP filter, IEEE 802.1X, digest authentication, user access log, TLS1.2, AES - 256, SSH/Telnet closed, FTP disabled. Protocol - DHCP, UDP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, SMTP, SSL/TLS, TCP/IP, Secure Real-Time Transport Protocol (SRTP), Bonjour, SNMP and Secure shell (SSH) supported protocol. RoHS, WEEE, ISO-14001 and REACH compliant, UL/EN OR equivalent BIS/TECH/STQC or any indian standards as applicable, CE, FCC certified. duly erected in position on wall/ceiling/false ceiling/provided pole (mounting height not more than 5 meter) etc with all accessories etc complete as perspecification no. CCTV-CAM</p>	Each

5.	<p>Supplying & erecting of High definition 4/5 Megapixel IP IR Dome Camera with following features Image Sensor : minimum 1/2.8" Progressive Scan CMOS, Video Resolution : minimum 2592 x 1520 Video Compression : H.264, H.265 or higher, at least Three individually configurable stream, Frame rate : minimum 25 fps at all resolutions, WDR : minimum 120 dB Wide Dynamic Range, ONVIF profile conformant, minimum IR distance : 50m, Lens Type : 2.8/4/6 mm Lens, fixed focal, Field of View : 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 129° 4 mm, horizontal FOV 86°, vertical FOV 47°, diagonal FOV 102° 6 mm, horizontal FOV 55°, vertical FOV 29°, diagonal FOV 65° Lux sensitivity - minimum 0.2 Lux at color, minimum 0.05 Lux at Black & White, 0.0 Lux (IR) Night Vision Distance minimum IR - 50m. Camera minimum Adjustment Angles - Pan : 350°, Tilt : 72°, Rotate : 350°. Power Supply : Support 12VDC & PoE, IP67, IK10 - Vandal Resistant. Built in micro SD/SDHC/SDXC card slot of minimum 128 GB, Built in microphone. minimum Input/Output - Audio in × 1, Audio Out × 1, Alarm in × 1, Alarm Out × 1. Image Settings : Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance. Image Enhancements : Day/Night-Auto (ICR)/Color/Black & White, 3D Digital Noise Reduction, Automatic White Balance, Automatic Gain Control, Backlight Compensation, Highlight Compensation. Events : Privacy Masking, Motion detection, Scene change detection, Face capture, Video tampering, audio exception detection, Region entrance detection, Region exiting detection. Operating temperature (-30 to 60° C) . Security - User account and password protection, HTTPS, IP filter, IEEE 802.1X, digest authentication, user access log, TLS1.2, AES - 256, SSH/Telnet closed, FTP disabled. Protocol - DHCP, UDP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, SMTP, SSL/TLS, TCP/IP, Secure Real-Time Transport Protocol (SRTP), Bonjour, SNMP and Secure shell (SSH) supported protocol. RoHS, WEEE, ISO-14001 and REACH compliant, UL/EN OR equivalent BIS/TECH/STQC or any indian standards as applicable, CE, FCC certified. duly erected in position on wall/ceiling/false ceiling/provided pole (mounting height not more than 5 meter) etc with all accessories etc complete as per specification no. CCTV-CAM.</p>	Each
6.	<p>Supplying, fixing, and configuring 24 port 10/100M un-managed standalone switch compliant with IEEE 802.3 standards as per specification complete.</p>	Each
7.	<p>Supplying, fixing, and configuring 24-port 10/100M un-managed 10/100/1000 base-T gigabit switches compliant with IEEE 802.3 standards as per specification complete.</p>	Each

2. दर पत्रक सादर करण्याची दिनांक वेळ व पत्ता:

- सीलबंद लिफाफ्यामध्ये दरपत्रके सादर करण्याची दिनांक व वेळ :- दिनांक . ०६ / ..०५ / 2026 वेळ सकाळी 10.00 ते दिनांक .16.. / ०५ / 2026 सायंकाळी वेळ 5.00 वाजेपर्यंत.
- दरपत्रके सादर करणे करिता पत्ता : कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव.
- दरपत्रके उघडण्याची वेळ : / ०५.. / 2026 सकाळी वेळ 11:00 वाजता.

3. अटी व शर्ती:

1. दरपत्राकतील दर फक्त अंदाजपत्रक तयार करण्यासाठी वापरण्यात येतील.
2. कामाची सविस्तर माहिती व तांत्रिक तपशील कार्यकारी अभियंता (बां), बांधकाम विभाग, जिल्हा परिषद धाराशिव या कार्यालयाकडून प्राप्त करून घेण्यात यावी.
3. निविदाधारकांनी कामाची जागा, वाहतूक, मजुरी खर्च व साहित्य उपलब्धतेचा स्वतः अभ्यास करावा.
4. सर्व उपकरणे व काम MNRE / BIS / IEC तसेच इतर लागू असलेल्या मानकांनुसार असणे आवश्यक आहे.
5. दरामध्ये सामग्रीचा पुरवठा, स्थापनेपासून ते चाचणी पर्यंतचे सर्व काम, वाहतूक, विमा, वॉरंटी / गॅरंटी व संपूर्ण देखभाल करार (CMC) समाविष्ट असावा.
6. सर्व दर G.S.T. वगळून देण्यात यावे.
7. पुरवठाधारक/ निविदाधारक हा Manufacturer/Integrator/Supplier/Developer आहे याची खात्री करणे करिता विभागाच्या मागणीनुसार आवश्यक दस्तऐवज सादर करणाऱ्यात यावे.
8. जिल्हा परिषद, धाराशिव दिलेल्या वस्तूंचे दर , गुणवत्तेची व तांत्रिक मानकांची पूर्तता तपासण्याचा अधिकार राखून ठेवला आहे.
9. खोटी अथवा दिशाभूल करणारी माहिती सादर केल्यास दरपत्रक फेटाळले जाईल व आवश्यक कार्यवाही करण्यात येईल याची नोंद घेण्यात यावी.
10. सदर बाबत कोणताही तंटा अगर वाद निर्माण झाल्यास त्याबाबत कोणत्याही न्यायालयात दावा दाखल करता येणार नाही. याबाबत कार्यकारी अभियंता (बां) , बांधकाम विभाग, जिल्हा परिषद धाराशिव किंवा जिल्हा परिषद धाराशिव मधील सक्षम प्राधिकारी यांचा निर्णय अंतिम राहिल.
11. दरपत्रक दिलेल्या विहित नमुन्यातच आणि पाकिटावर विषय नमूद करून सादर करणे आवश्यक आहे.
12. मुदत संपल्यानंतर प्राप्त होणाऱ्या कोटेशनचा विचार केला जाणार नाही.
13. कार्यकारी अभियंता (बां) , बांधकाम विभाग, जिल्हा परिषद धाराशिव किंवा जिल्हा परिषदेतील सक्षम प्राधिकारी यांनी कोणतीही कोटेशन नाकारण्याचा/स्वीकारण्याचा अधिकार राखून ठेवला आहे.

कार्यकारी अभियंता (बां)
बांधकाम विभाग, जिल्हा परिषद,
धाराशिव

• दरपत्रक सादर करावयाचा नमुना :

(ठेकेदार/ पुरवठादार लेटर हेड)

Date : / / 2026

दरपत्रक

प्रती,

मा. कार्यकारी अभियंता (बां)

बांधकाम विभाग,

जिल्हा परिषद , धाराशिव

विषय : दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी सीलबंद दरपत्रक मागविणे बाबत

संदर्भ : आपले दरपत्रक मागणी पत्र

महोदय,

उपरोक्त विषयास अनुसरून सादर कि, संदर्भिय पत्रान्वये दरसूचीबाह्य बाबींचे दर निश्चित करण्यासाठी सीलबंद दरपत्रके मागविण्यात आले आहेत. त्यानुसार खलील प्रमाणे दरसूची बाह्य बाबींचे दर सादर करित आहोत. सादर दर हे सामग्रीचा पुरवठा, स्थापनेपासून ते चाचणी पर्यंतचे सर्व काम, वाहतूक, विमा, वॉरंटी / गॅरंटी व संपूर्ण देखभाल करार (CMC) यांचा विचार करून निश्चित केलेले आहेत.

Sr. No	Details of Item (Non – CSR)	Unit	Rate
1.	Supplying, installing, testing & commissioning of 16/20 Ch. Network Video Recorder (NVR), suitable for 2 MP cameras only with HDMI/VGA outputs provided HDMI output of 4K resolution or VGA output with output up to 1920 × 1080. Support H.265 or higher, H.264, MJPEG, Incoming Bandwidth 160Mbps with minimum 2 SATA Hard Disks, ANR Technology, 2 SATA interfaces for 2 HDDs and capacity of each HDD up to 8TB, minimum 02 USB port, Alarm I/O 4/1, RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface, support multi brand network Cameras, ONVIF conformance, Multiple network monitoring: Web viewer. support protocol TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS. RoHS, UL, CE, FCC certified. duly erected in provided U Rack with wiring connections, tagging and programming etc. complete as per specifications no. CCTV-NVR	Each	
2.	Supplying & erecting 43" professional LED display with 1920*1080 (Full HD) Display, suitable for 16/32 channel NVR and following features Brightness: minimum 500 Cd/m2 Contrast Ratio: minimum 1000:1 Viewing angle: 178/178 deg. Response time: maximum 8 ms Inputs: HDMI, VGA, BNC,USB, Audio In, Built-in speakers maximum 10 W, Suitable to operate on 100-240 V 50 Hz AC supply and 24/7 Duty Cycle duly erected on wall or table top with standard accessories like wall mount stand and wiring connections etc. complete as per specifications no. CCTV-MON	Each	

3.	<p>Supplying & erecting 4 TB internal Surveillance HDD suitable for SATA Port of NVR, interface transfer rate 6 GB/S, Maximum sustained transfer rate 150MB/Sec to 180MB/S. Drive bay supported 08+, Cameras supported up to 64, Cache (MB) 64, Load/Unload Cycle -3000000, Work Load Rating per Year 180TB, MTBF 1000000 Hrs. HTTPS. RoHS, UL, CE certified, duly erected in position in provided NVR as per specification no. CCTV-HDD</p>	Each	
4.	<p>Supplying & erecting of High definition 4/5 Megapixel IP IR Bullet Camera with following features Image Sensor : minimum 1/2.8" Progressive Scan CMOS, Video Resolution : minimum 2592 x 1520 Video Compression : H.264, H.265 or higher, at least Three individually configurable stream, Frame rate : minimum 25 fps at all resolutions, WDR : minimum 120 dB Wide Dynamic Range, ONVIF profile conformant, minimum IR distance : 50m, Lens Type : 2.8/4/6 mm Lens, fixed focal, Field of View : 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 129° 4 mm, horizontal FOV 86°, vertical FOV 47°, diagonal FOV 102° 6 mm, horizontal FOV 55°, vertical FOV 29°, diagonal FOV 65° Lux sensitivity - minimum 0.2 Lux at color, minimum 0.05 Lux at Black & White, 0.0 Lux (IR) Night Vision Distance minimum IR - 50m. Camera minimum Adjustment Angles - Pan : 350°, Tilt : 72°, Rotate : 350°. Power Supply : Support 12VDC & PoE, IP67, IK10 - Vandal Resistant. Built in micro SD/SDHC/SDXC card slot of minimum 128 GB, Built in microphone. minimum Input/Output - Audio in × 1, Audio Out × 1, Alarm in × 1, Alarm Out × 1. Image Settings : Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance. Image Enhancements : Day/Night-Auto (ICR)/Color/Black & White, 3D Digital Noise Reduction, Automatic White Balance, Automatic Gain Control, Backlight Compensation, Highlight Compensation. Events : Privacy Masking, Motion detection, Scene change detection, Face capture, Video tampering, audio exception detection, Region entrance detection, Region exiting detection. Operating temperature (-30 to 60° C) . Security - User account and password protection, HTTPS, IP filter, IEEE 802.1X, digest authentication, user access log, TLS1.2, AES - 256, SSH/Telnet closed, FTP disabled. Protocol - DHCP, UDP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, SMTP, SSL/TLS, TCP/IP, Secure Real-Time Transport Protocol (SRTP), Bonjour, SNMP and Secure shell (SSH) supported protocol. RoHS, WEEE, ISO-14001 and REACH compliant, UL/EN OR equivalent BIS/TECH/STQC or any indian standards as applicable, CE, FCC certified. duly erected in position on wall/ceiling/false ceiling/provided pole (mounting height not more than 5 meter) etc with all accessories etc complete as perspecification no. CCTV-CAM</p>	Each	

5.	<p>Supplying & erecting of High definition 4/5 Megapixel IP IR Dome Camera with following features Image Sensor : minimum 1/2.8" Progressive Scan CMOS, Video Resolution : minimum 2592 x 1520 Video Compression : H.264, H.265 or higher, at least Three individually configurable stream, Frame rate : minimum 25 fps at all resolutions, WDR : minimum 120 dB Wide Dynamic Range, ONVIF profile conformant, minimum IR distance : 50m, Lens Type : 2.8/4/6 mm Lens, fixed focal, Field of View : 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 129° 4 mm, horizontal FOV 86°, vertical FOV 47°, diagonal FOV 102° 6 mm, horizontal FOV 55°, vertical FOV 29°, diagonal FOV 65° Lux sensitivity - minimum 0.2 Lux at color, minimum 0.05 Lux at Black & White, 0.0 Lux (IR) Night Vision Distance minimum IR - 50m. Camera minimum Adjustment Angles - Pan : 350°, Tilt : 72°, Rotate : 350°. Power Supply : Support 12VDC & PoE, IP67, IK10 - Vandal Resistant. Built in micro SD/SDHC/SDXC card slot of minimum 128 GB, Built in microphone. minimum Input/Output - Audio in × 1, Audio Out × 1, Alarm in × 1, Alarm Out × 1. Image Settings : Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance. Image Enhancements : Day/Night-Auto (ICR)/Color/Black & White, 3D Digital Noise Reduction, Automatic White Balance, Automatic Gain Control, Backlight Compensation, Highlight Compensation. Events : Privacy Masking, Motion detection, Scene change detection, Face capture, Video tampering, audio exception detection, Region entrance detection, Region exiting detection. Operating temperature (-30 to 60° C) . Security - User account and password protection, HTTPS, IP filter, IEEE 802.1X, digest authentication, user access log, TLS1.2, AES - 256, SSH/Telnet closed, FTP disabled. Protocol - DHCP, UDP, HTTP, HTTPS, NTP, DNS, RTP, RTSP, SMTP, SSL/TLS, TCP/IP, Secure Real-Time Transport Protocol (SRTP), Bonjour, SNMP and Secure shell (SSH) supported protocol. RoHS, WEEE, ISO-14001 and REACH compliant, UL/EN OR equivalent BIS/TECH/STQC or any indian standards as applicable, CE, FCC certified. duly erected in position on wall/ceiling/false ceiling/provided pole (mounting height not more than 5 meter) etc with all accessories etc complete as per specification no. CCTV-CAM.</p>	Each	
6.	Supplying, fixing, and configuring 24 port 10/100M un-managed standalone switch compliant with IEEE 802.3 standards as per specification complete.	Each	
7.	Supplying, fixing, and configuring 24-port 10/100M un-managed 10/100/1000 base-T gigabit switches compliant with IEEE 802.3 standards as per specification complete.	Each	

दर पत्रकासह सादर करण्यात येत असलेल्या बाबीचा तपशील.

1.
2.
3.
4.

आपला विश्वासू,
(सही व शिक्का)
(ठेकेदार/ पुरवठादार यांचे नाव व पत्ता)