

जिल्हा व सत्र न्यायालय, पुणे

जाहीर निविदा — नोटिस

विषय :- जिल्हा न्यायालय, पुणे यांच्या आस्थापणेनवरील न्यायालयाकरीता व कार्यालयासाठी लोखंडी कपाट व लोखंडी रॅक खरेदी प्रक्रिया राबविण्यासाठी स्थानिक बाजारपेठेतून दरपत्रक मिळणेबाबत...

उपरोक्त विषयांस अनुसरून आपणांस कळविण्यात येते कि, जिल्हा न्यायालय, पुणे यांच्या आस्थापणेनवरील न्यायालयाकरीता व कार्यालयासाठी लोखंडी कपाट व लोखंडी रॅक खरेदी करणेस स्थानिक बाजारपेठेतून दरपत्रक मागणी करावयाचे आहे. त्यांचा तपशील खालील प्रमाणे :-

पुरवठादारांचे नांव व पत्ता :-

अ. क्र.	वस्तूचा तपशील	एकूण नगांची संख्या	प्रत्येक नगाची किंमत	प्रत्येक नगाचे किंमतीवरील सर्व करांची रक्कम	सर्व करांसह प्रत्येक नगाची किंमत	सर्व करांसह एकूण नगांची किंमत
१	लोखंडी कपाट — तपशील पुढील प्रमाणे	६०				
	Construction Type		Welded			
	Installaton		Free Standing			
	Pedestal		Yes			
	Pedestal fitted with		3 mm Teflon Bush			
	Pedestal height (±5 mm)		125 mm			
	Door type		Hinged			
	Number of door		2			
	Number of hinges for each door		3			
	Door stiffener up to full dooor height provided		Yes			
	Shelves required		Fixed			
	Number of shelves		4			
	Uniformly distributed load for shelves		60 kgs.			
	Wardrobe by Style		Full size			
	Colour of finish		Ash Grey			
	Steel sheet material		CRCA sheets conforming to grade CRI of IS 513(part-1):2016 (with lates amendment)			
	Screws		Conforming to IS 1365			
	Almirah height (excluding the height of pedestal) ±5 mm		1980 mm			
	Almirah width ±5 mm		910 mm			
	Almirah depth ±5 mm		440 mm			
	Locker inside height ±5 mm		290 mm			
	Locker inside width ±5 mm		Full size of almirah width			
	Side, Back, Top, Bottom sheet thickness		0.8 mm			
	Shelves shteet thickness		0.6 mm			

अ. क्र.	वस्तूचा तपशील	एकूण नगांची संख्या	प्रत्येक नगाची किंमत	प्रत्येक नगाचे किंमतीवरील सर्व करांची रक्कम	सर्व करांसह प्रत्येक नगाची किंमत	सर्व करांसह एकूण नगांची किंमत																																						
	<table border="1"> <tr><td>Door metal stiffener thickness</td><td>0.8 mm</td></tr> <tr><td>Pedestal shet thickness</td><td>0.8 mm</td></tr> <tr><td>Hinges sheet thickness</td><td>1.6 mm</td></tr> <tr><td>Locker door sheet thickness</td><td>0.9 mm</td></tr> <tr><td>Handle size</td><td>12 cm</td></tr> <tr><td>Steel almirah lock / locker lock</td><td>Six lever lock</td></tr> <tr><td>Material of lock</td><td>Brass and steel finish</td></tr> <tr><td>Duplicate Keys for each</td><td>Yes</td></tr> <tr><td>Keys material for each lock</td><td>Brass and steel finish</td></tr> <tr><td>Steel Almirah locking mechanism</td><td>A three way bolting devie controlled by a lock</td></tr> <tr><td>Door handle material for locker</td><td>Stainles steel</td></tr> <tr><td>Handle material for locker</td><td>Brass base alloy</td></tr> <tr><td>Locker locking mechanism</td><td>Two way bolting sytem controlled by the lock</td></tr> <tr><td>Finish coat with enamels</td><td>Stoving enamel</td></tr> </table>	Door metal stiffener thickness	0.8 mm	Pedestal shet thickness	0.8 mm	Hinges sheet thickness	1.6 mm	Locker door sheet thickness	0.9 mm	Handle size	12 cm	Steel almirah lock / locker lock	Six lever lock	Material of lock	Brass and steel finish	Duplicate Keys for each	Yes	Keys material for each lock	Brass and steel finish	Steel Almirah locking mechanism	A three way bolting devie controlled by a lock	Door handle material for locker	Stainles steel	Handle material for locker	Brass base alloy	Locker locking mechanism	Two way bolting sytem controlled by the lock	Finish coat with enamels	Stoving enamel															
Door metal stiffener thickness	0.8 mm																																											
Pedestal shet thickness	0.8 mm																																											
Hinges sheet thickness	1.6 mm																																											
Locker door sheet thickness	0.9 mm																																											
Handle size	12 cm																																											
Steel almirah lock / locker lock	Six lever lock																																											
Material of lock	Brass and steel finish																																											
Duplicate Keys for each	Yes																																											
Keys material for each lock	Brass and steel finish																																											
Steel Almirah locking mechanism	A three way bolting devie controlled by a lock																																											
Door handle material for locker	Stainles steel																																											
Handle material for locker	Brass base alloy																																											
Locker locking mechanism	Two way bolting sytem controlled by the lock																																											
Finish coat with enamels	Stoving enamel																																											
२	लोखंडी रॅक – तपशील पुढील प्रमाणे	१००																																										
	<table border="1"> <tr><td>Configuration</td><td>With 5 – shelf (including top helf)</td></tr> <tr><td>Type of Rack</td><td>Open from all sides</td></tr> <tr><td>Design/Shape of rack</td><td>Rectangular</td></tr> <tr><td>Frame type</td><td>Perfectly in upright and straight positon</td></tr> <tr><td>Shape os support structure</td><td>Rectangular hollow tye</td></tr> <tr><td>Shelves fitted</td><td>At the right angles to siders and to be parallel to each other</td></tr> <tr><td>Ground clearance mm</td><td>75 mm</td></tr> <tr><td>Mode of supply</td><td>Knocked Down to be assembled at consignee site by consignee himself</td></tr> <tr><td>Shelf material</td><td>Stainless steel grade 316 galvanized</td></tr> <tr><td>Shelf material thickness</td><td>1.0 mm</td></tr> <tr><td>Support structure material</td><td>Stainless steel Grade 316 galvanized</td></tr> <tr><td>Support structure material thickness</td><td>3.0 mm</td></tr> <tr><td>Width of shelf rack ± 10 mm</td><td>1065 mm</td></tr> <tr><td>Depth of shelf rack ± 10 mm</td><td>405 mm</td></tr> <tr><td>Hight of shelf rack ± 10 mm</td><td>1675 mm</td></tr> <tr><td>Height of support structure ± 10 mm</td><td>1550 mm</td></tr> <tr><td>Size of support structure</td><td>35 mm x 40 mm</td></tr> <tr><td>Ends of the sides / Shelf</td><td>To be double flod ater cutting</td></tr> <tr><td>Dressing of shelf rack</td><td>Surface free from crack</td></tr> </table>	Configuration	With 5 – shelf (including top helf)	Type of Rack	Open from all sides	Design/Shape of rack	Rectangular	Frame type	Perfectly in upright and straight positon	Shape os support structure	Rectangular hollow tye	Shelves fitted	At the right angles to siders and to be parallel to each other	Ground clearance mm	75 mm	Mode of supply	Knocked Down to be assembled at consignee site by consignee himself	Shelf material	Stainless steel grade 316 galvanized	Shelf material thickness	1.0 mm	Support structure material	Stainless steel Grade 316 galvanized	Support structure material thickness	3.0 mm	Width of shelf rack ± 10 mm	1065 mm	Depth of shelf rack ± 10 mm	405 mm	Hight of shelf rack ± 10 mm	1675 mm	Height of support structure ± 10 mm	1550 mm	Size of support structure	35 mm x 40 mm	Ends of the sides / Shelf	To be double flod ater cutting	Dressing of shelf rack	Surface free from crack					
Configuration	With 5 – shelf (including top helf)																																											
Type of Rack	Open from all sides																																											
Design/Shape of rack	Rectangular																																											
Frame type	Perfectly in upright and straight positon																																											
Shape os support structure	Rectangular hollow tye																																											
Shelves fitted	At the right angles to siders and to be parallel to each other																																											
Ground clearance mm	75 mm																																											
Mode of supply	Knocked Down to be assembled at consignee site by consignee himself																																											
Shelf material	Stainless steel grade 316 galvanized																																											
Shelf material thickness	1.0 mm																																											
Support structure material	Stainless steel Grade 316 galvanized																																											
Support structure material thickness	3.0 mm																																											
Width of shelf rack ± 10 mm	1065 mm																																											
Depth of shelf rack ± 10 mm	405 mm																																											
Hight of shelf rack ± 10 mm	1675 mm																																											
Height of support structure ± 10 mm	1550 mm																																											
Size of support structure	35 mm x 40 mm																																											
Ends of the sides / Shelf	To be double flod ater cutting																																											
Dressing of shelf rack	Surface free from crack																																											

अ. क्र.	वस्तूचा तपशिल	एकूण नगांची संख्या	प्रत्येक नगाची किंमत	प्रत्येक नगाचे किंमतीवरील सर्व करांची रक्कम	सर्व करांसह प्रत्येक नगाची किंमत	सर्व करांसह एकूण नगांची किंमत
	and distortion					
	Packing	Bubbled sheet packing				
	Weight in kg	15 kilogram				
	Warranty period	1 Year				

पुरवठादारांचे नांव व पत्ता

दूरध्वनी क्रमांक / मोबाईल क्रमांक

सही शिक्का दिनांकासह

तरी वरीलप्रमाणे जिल्हा न्यायालय, पुणे यांच्या आस्थापणेनवरील न्यायालयाकरीता व कार्यालयासाठी लोखंडी कपाट व लोखंडी रॅक आपलेकडील जागेपोहोच सर्व करांसहचे दरपत्रक मा. प्रमुख जिल्हा न्यायाधीश, जिल्हा व सत्र न्यायालय, पुणे यांचे नावे शनिवार, दिनांक ०१.०३.२०२५ रोजी दुपारी २.०० वाजपर्यंत सादर करण्यात यावे.

* उपरोक्त नमुद नगांच्या संख्येत वाढ आथवा घट होऊ शकते, त्याबाबतचे सर्व अधिकारी या न्यायालयाकडे राखीव असून त्याबाबत कोणत्याही तक्रारीची दखल घेण्यात येणार नाही.

हुकूमवरून,

(२) १३/११
१३/२

प्रबंधक,

जिल्हा न्यायालय, पुणे

दिनांक:- १३/०२/२०२५.