

പിഎം. ശ്രീകേന്ദ്രീയവിദ്യാലയം,പട്ടം,തിരുവനന്തപുരം पीएम श्री केन्द्रीय विद्यालय, पटटम,तिरुवनन्तपुरम,*केरलम-६९५००४* PM SHRI KENDRIYA VIDYALAYA PATTOM, THIRUVANANTHAPURAM-695004

UNDER MINISTRY OF EDUCATION, GOVT OF INDIA दुरभाष/:PHONE NO.0471-2445854/2441816 - Fax: 0471.2441815

CBSE Affiliation No.900004 - SCHOOL NO: 79027



फ़केवी./पट्टम .प्रपा/2-21/2024-25/



दिनांक: 03/02/2025

Sub: INVITING QUOTATIONS FOR SUPPLY AND INSTALLATION OF CCTV SURVEILLANCE SYSTEM INLCUDING CABLING, NVR AND OTHER ACCESSORIES AT PM SHRI KENDRIYA VIDYALAYA PATTOM THIRUVANANTHAPURAM

- 1. PM Shri Kendriya Vidyalaya Pattom Thiruvananthapuram, An Autonomous Body under Ministry of Education, Government of India, is an Education institution under Kendriya Vidyalaya Sangathan a Society registered under Societies 'Registration Act 1860.The Sangathan administers the Scheme of Kendriya Vidyalaya set up for imparting education to the children of transferable Central Govt. Employees among others.
- 2. Sealed competitive quotations from firms who are having valid license & registration are invited by the Principal PM Shri Kendriya Vidyalaya Pattom Thiruvananthapuram for supply and installation of CCTV Surveillance system as per the schedule/ details attached.

TECHNICALSPECIFICATIONFORCCTVCAMERA&ACCESSORIES

SI	Products	Product Specification		Rate / Unit
No				
01		Image Sensor Minimum Illumination Effective Pixels Shutter Speed White Balance Lens Lens Type	4MPPSCMOSImageSensor(0.84567cm) 0.0Jlux@F2.0(COlor,30IRE)0.001lux@F2.0(B/W,30IRE)0lux (IRon) 25G0(H) 1440(V) Auto/Manual,1/31/100000s Auto;natura!;streetlamp;outdoor; manual; regional custom 2.8mm	Onit
		Mount Type MaxAperture IrisControl Close Focus Distance	Wide range lens M12 F2.0 Fixed 1.4m	
		DORI Distance	85.2m(Detect)34.1m(Observe)17m(Recognize)8.5m (Identify)	
		Gain Control(AGC) Video Compression Angle of View Back Light Comp. S/N Ratio	Auto H.265/SmartH.264+/H.264/H.264B/MjPEG H: 76°; V: 40"; D:92' BLC/ HLC/ DWDR >56dB Main stream: 2560 1440@ (1-25/30 hps) Su b stream: 704x	
		Video Streaming	576@ (1-25 lps)/704•480@(1 -30lps)*The values above are the max. frame rates of each stream; for multiple streams, the	
		Resolution	Values will be subjected to the total encoding capacity. 4M(2S60^1440),3M(23041296)1080p(1920^1080)1.3M (1280•960);720p(1280 720);D1(704•S76/704•480);VGA (640•480);CIF(352•288/352•240)	
	CAMER A IP 4MP IP DOM	Mirror Motion Detection Privacy Mask ICR	Support Off/On(4area,Rectangle) a areas Auto(ICR)/Color/B/W H.264:32kbps-4096kbpsH.265:12kbps-4096kbps	

		Video Bit Rate	3D-DNR
		Noise Reduction	CBR/VBA
		Bit Rate Control	IPv4;IPV6;HTTP;TCP;UDP;ARP;RTP;RTSP;RTCP;SMTP;FTP;
		Protocol	DHCP; DNS; DDNS; NTP;
			0°/180"
		Image Rotation	
			DI 45/40/400D T\
			RI-45(10/100Base-T) Network disconnection; IP conflict; illegal access; motion
		Ethernet	detection; video tampering; security exception
		Alarm Event	Configuration encryption; Trusted execution; Digest; Security
			logs: HTTPS; Trusted upgrade; WSSE: Trusted boot: Account
		Cyber Security	lockout; Generation and importing ofX.509 certification; Video
			encryption
		IR Distance	IR Range of 30Mtr.,Smart IR
		IN Distance	
			IE, Chrome, Firefox
		Browser	FTP (1995) 1995)
		Edge Storage	40'Cto+50"C(-40°Fto+122°F)
		Operating Temperature	·0E0/
		Operating Humidity	<95%
		Storage	-40°Cto+60°C(-40°Fto+140°F) 195%
		Temperature	DC12V,PoE
		Storage Humidity	DO124,1 GE
		Power Source	Basic: 1.4 W(12 VDC); 2.1 W(PoE) Max.(ICR switch + IP
		Power Consumption	intensity):3.0 W (12 VDC);402 W(PoE)
			IP67
		Moothorproof	
		Weatherproof Standard	Metal
		Casing	198.9mm * 80.2 mm* 76.2 mm(7.83"*3.16" *3.00")(L* W*H)
		Dimension	0.460kg
		Weight	
02		Two-way Talk	1*RCA input: Audio Input/Audio Output
		Video Output	1* VGA output, 1* HDMI output bth VGA and HDMI
		Channel	32channelVideo, (Upto 8 MB support)
		Bandwidth	160Mbps;Storag: 128 Mbps; Forward: 48 Mbps
		Incoming	The state of the s
		Motion Detection	Zones:396(22*18)
	NETWO	Smart Phone	Android Phone, OIS
	RK	Hard Disk	2 SATA III ports, up to 10 TB for a single HDFD Maximum 18-20 TB
	VIDEO RECOR	Recording Mode	as per ETA Manual; record; alarm recording; SMD recording; smart recording
	DER	Trecording Mode	Time/Date, MD and Exact Search(aacurate to second), Smart
	32'CHA	Search Mode	search
	NNELS		USB Device/Network
	4K	Backup Mode	Play/pause/stop/slow/quick/backward/by frame Full screen,
	CP Plus	Playback	Backup (video clip/file), partial zoom in, and audio on/off
		Ethornot	1 * RJ-45,10/100/1000 Mbps self-adaptive Ethernet port
		Ethernet Interface Ports	2 USB Ports (1* front USB2.1; 1*back USB2.0) HTTP;HTTPS;TCP/IP;IPv4/IPv6;
		Protocols	UPnP;SNMP;RTSP;UDP;SMTP;NTP;DHCP;DNS;IP
			B Filter; DDNS; FTP; Alarm Server; IP Search, P2P, auto register,
			RTSP,ONVIF(profile T/S/G); CGL; SDK
		İ	DC12V/4A
		Power Supply	<5.6 W(HDD not included, idling)
		Power Consumption	<5.6 W(HDD not included, idling)
03		Power Consumption Working Temp	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F)
03		Power Consumption	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex
03		Power Consumption Working Temp	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F)
03		Power Consumption Working Temp Switch Capacity Uplink Ports PoE Power Budget	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex 16 channel & 8 Channel 2, 1000Mpbs; Transmission Distance:0-100m 48W
03		Power Consumption Working Temp Switch Capacity Uplink Ports PoE Power Budget Anti-thunder Level	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex 16 channel & 8 Channel 2, 1000Mpbs; Transmission Distance:0-100m 48W Common mode :2KV Differential mode: 2KV
03		Power Consumption Working Temp Switch Capacity Uplink Ports PoE Power Budget Anti-thunder Level ESD	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex 16 channel & 8 Channel 2, 1000Mpbs; Transmission Distance:0-100m 48W
03		Power Consumption Working Temp Switch Capacity Uplink Ports PoE Power Budget Anti-thunder Level	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex 16 channel & 8 Channel 2, 1000Mpbs; Transmission Distance:0-100m 48W Common mode :2KV Differential mode: 2KV
03		Power Consumption Working Temp Switch Capacity Uplink Ports PoE Power Budget Anti-thunder Level ESD	<5.6 W(HDD not included, idling) -10°C to +55°C (+10 ° F to + 131 ° F) 12 Gbps Full deplex 16 channel & 8 Channel 2, 1000Mpbs; Transmission Distance:0-100m 48W Common mode :2KV Differential mode: 2KV

				1
	FAST ETHER	Transmission Distance PoE Ports PoE Power Supply	Disconnected Light is disconnected Light flash quickly: Data Transmitting 16 1Gbps	
	NET POE SWITCH	PoE Standard Packet Frwarding Rate MAC Address List	4, 1000Mbps; Rj45 ports; Max. 30W Output of Single PoE Port Transmission distance:0-1 00m 1/2(+),3/6(-)	
		Power Source Power Consumption Operating	IEEE802.3al IEE E802.3at 1.488ttlpps/port	
		Temperature Humanity Storage	2K	
		Temperature	Built-in Power Supply, Input; 110-264V AC, 50/60H2 <5W	
			10'c50"c	
			1 096-9570, non-condensing -40'c-70'c	
04	SURVIE LLA	Device Device Type	Surveillance Systems 3.5 inch HDD	
	NCE	Drive Capacity	8TB	
	HARD DISK	Interface Cache Memory	SATA 256 MB	
		Transfer Rate Non-recoverable	210 Mbps 1 per 10E15	
		Read Error	·	
		Reliability Form Factor	300000 (Lcrad/Unload Cycles), 1000000 hours {Mean Time between	
05	NETWO	Category : 6 UTP Solid	3.5 inch	
03	RK	Conductor : Conductor	: 23 AWG (Solid)	
	TWISTE D	Conductor Meta: Cond Meta: Bare Copper	uctor	
	CABLE UTP	insulation Material: HD Resistance Unbalance		
	OIP	Capacitance Unbal and		
		Delay Skew: <45nS Gauge: 52		
06	HDMI Cable	8K resolution support h	HDMI cable	
07	USB extender			
08	RJ 45 CONNE		Cable Outer Diameter {OD} < 6.2 mm	
	CT oRs		e Range-40" to 3.85"F (-40" to 85"C	
09	ETECT RIC	Product Category Size of Conductor	1 Core Cables 1sq mm	
	WIRE	Core	1 Core	
		Length Conductor Material	90 mtr Copper	
		Colour insulation Material	Black/Red/Green PVC	
		Current Rating AC	6-15 Amp	
10	RACK WALL		king Rack, Size: 1000x600x600 mm (hxwxd) lication. Use To Hold Networking Equipment Outside Servers Like	
	MOUNTI	Switches, Patch Panel	s, And Routers.	
	N G	coated.	ount. Size. 1000x600x600 mm {F*xWxD) Finishing Type. Powder	
11	INSTAT	Rack Standard. Equipr	ment Mounting. as per location allocated and proper installation guideline for	
' '	LAT	safety and security.	2 ps. 1554.1511 anstalled and propor motunation galdeline for	
	ION AND	10		
	SERVIC			

	Е		
12	CABLIN G	Pipe, Conduits and other accessories with labour for fixing ISI certified pipe	

3. Terms and conditions

- a) The contract shall be for the work of the mentioned items for PM Shri Kendriya Vidyalaya, PATTOM Thiruvananthapuram. The bidder shall quote the rates for items of work in the attached format (Annexure I). Corrections, if any, shall be made by crossing out ,initialing with date and rewriting.
- b) All taxes, duties and other levies payable by the bidder, shall be included in the total price. They shall be quoted separately. No additional payment will be done for anything that is not quoted.
- c) Theratesquotedbythebiddershallbefixedforthedurationofthecontracti.e.foroneyear from the date of award of the contract.
- d) Each bidder shall submit only one quotation.
- e) Quotations are not acceptable if submitted through e-mail/Faxetc
- f) The bid should be submitted along with EMD for Rs. 5000/- (Rupees Five Thousand Only) through NEFT/RTGS or bank draft in favour of "Principal Kendriya Vidyalaya PATTOM Thiruvananthapuram VVN A/c" payable at Thiruvananthapuram. The EMD paid will be refunded in the case of unsuccessful bidders within 90 days from the date of opening of Quotations.
- g) The firm should enclose supporting documents regarding registration of GST/IT—PAN/TAN /Registration Certificates from department concerned without fail.

4. Validity of quotations

The quotation shall remain valid for a period not less than One year after the deadline specified for submission of quotations. It is also mentioned that if the buyer satisfies the performance of Bidder (L1), the period of validity can be extended for another 01year with the approval Chairman, VMC.

5. Evaluation of quotations

The Purchases will evaluate and compare the quotations determined to be substantially responsive, i.e., which are:

- a. Properly signed
- b. Confirm to the terms and conditions and specifications.

The evaluation would be done for all the items/services put together. The items/services for which no rates have been quoted would be treated as zero and the total amount would be computed accordingly, the bidder who has quoted for partial quantity of any one or more item(s) would be treated as non-responsive. The purchaser shall keep in mind that the rates quoted shall be competitive and do not in any manner whatsoever compromise with the quality of item and services to be provided by him as per the terms and conditions. PM Shri KV Pattom Thiruvananthapuram will award the contract to the responsive bidder whose total cost for all the items put together is the lowest. However, this does not restrict the purchaser from imposing any further conditions before awarding the contract.

6. Award of contract:

- a) The purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest price as mentioned above.
- b) The bidder whose bid is accepted will be notified of the award of the contract by the office prior to expiration of the quotation validity period.
- c) The Notification of Award shall be clearly specifying any change in the unit price or any other terms and conditions accepted.
- d) Normalcommercialwarranty/quaranteeshallbeapplicabletothesuppliedGoods/Services.

- e) Paymentshallbemadewithin15daysafterthesupplyiscompleted.
- f) Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of the contract.

6. Additional Terms and Conditions

- a) The awardee of the contract shall begin the work only after obtaining the APPROVAL OFTHE Work Monitoring Committee with regard to the quality of the Material to be used for the work.
- b) The tools for installing CCTVs and other accessories, ladders, etc. to be brought by the awardee and the rates quoted should include all these. At no cost, such materials shall be provided by the Vidyalaya.
- c) No material/ services for supply and installing CCTVs along with its accessories shall be provided by the Vidyalaya.
- d) Theawardeeofthecontractshallbeliabletocompensatethedamagescausedtothe Building or the materials in the building, if any, during the work.
- e) The awardee of the contract shall be liable to pay compensation/penalty if the said work is not completed within the stipulated time.
- f) TaxDeductedatSource(TDS)/GSTTDSwillbedeductedasperapplicableRates.

7. Last date and time of receipt of quotations:

The quotations and/or documents should be in sealed cover with super scribed on the envelop as "Quotations for supply and installation of CCTV surveillance system" and should reach in this Vidyalaya on or before 10 February2025 (1400 Hrs). The quotation shall be opened on the same day (10.02.2025) at 1430 Hrs. The representatives who choose to be present at the time of opening of quotations are invited to the institute to attend the proceedings.

भवदीय, (आरगिरिशंकरनतम्पि) प्राचार्य. केवीपट्टम